

# X-Panel 4343a FQI


a-Si X-ray flat panel detector



## Key Features

- Pixel pitch 140  $\mu\text{m}$
- Active Area 430 $\times$ 430mm
- The frame rate of Max. 12 fps (1x1) , Max. 24 fps (2x2)
- High dynamic range and a long lifetime among other benefits

X-Panel 4343a FQI is a fixed type and low noise X-ray flat panel detector. It is based on amorphous silicon (a-Si) technology that features a high dynamic range and a long lifetime among other benefits. X-Panel 4343a FQI has good image quality and a large dynamic range. Furthermore, it comes with multiple gain modes, that make it compatible with both high sensitivity and large dynamic range requirements. Optimized for industrial CT, casting, pipe welding applications.



# Technical Specifications

Technology	
Sensor	a-Si
Scintillator	GOS / Csl
Active Area	430 x 430 mm
Pixel Matrix	3072 x 3072
Pixel Pitch	140 $\mu$ m
AD Conversion	16 bits
Interface	
Data Interface	Optical Fiber
Exposure Control	Pulse Sync In / Pulse Sync Out
Work Mode	Software Mode / HVG Sync Mode / FPD Sync Mode
Frame speed	12fps(1x1) / 24fps(2x2)
Operating System	Windows7 / Windows10 OS 32 bits or 64 bits
Technical Performance	
Resolution	3.5 lp/mm
Energy Range	40~160KV / 350KV
Lag	0.8% @ 1st frame
Dynamic Range	$\geq$ 86dB
Sensitivity	620 lsb/uGy
SNR	49 dB @ (20000lsb)
MTF	72% @ (1 lp/mm) 44% @ (2 lp/mm) 25% @ (3 lp/mm)
DQE (2uGy)	66% @ (0 lp/mm) 42% @ (1 lp/mm) 28% @ (2 lp/mm)
Mechanical	
Dimension(H x W x D)	470 x 470 x 34 mm
Weight	9.5 kg / 13 kg
Sensor Protection Material	Carbon Fiber
Housing Material	Aluminum Alloy
Environmental	
Temperature Range	10~35°C (operating) ; -10~50°C (storage)
Humidity	30~70% RH (non-condensing)
Vibration	IEC 60068-2-64 Operation: 1G, 5-500Hz
Shock	IEC 60068-2-27 Operation: 2G, duration 11ms
Dust and Water Resistant	IPX0
Power	
Supply	100~240 VAC
Frequency	50/60 Hz
Consumption	17.5 W

