

X-Panel 4343a FTI-X

a-Si X-ray flat panel detector



Key Features

- Pixel pitch 100 μm
- Active Area 430 \times 430mm
- The frame rate of Max. 2 fps (1x1) , Max. 8 fps (2x2)
- High dynamic range and a long lifetime among other benefits

X-Panel 4343a FTI-X is a 43 x 43cm fixed type and low noise X-ray flat panel detector based on a-Si technology that features excellent sensitivity and high dynamic range modes among other benefits. X-Panel 4343a FTI-X has good image quality and a large dynamic range. It is an optimal solution in component counting , casting and pipe welding applications.



Technical Specifications

Technology	
Sensor	a-Si
Scintillator	GOS / CsI
Active Area	430 x 430 mm
Pixel Matrix	4288 x 4288
Pixel Pitch	100 μ m
AD Conversion	16 bits
Interface	
Data Interface	Gigabit Ethernet
Exposure Control	Pulse Sync In / Pulse Sync Out
Work Mode	Software Mode / HVG Sync Mode / FPD Sync Mode
Frame speed	2fps (1x1) / 8fps (2x2)
Operating System	Windows7 / Windows10 OS 32 bits or 64 bits
Technical Performance	
Resolution	5.0 lp/mm
Energy Range	40~160KV / 350KV
Lag	0.8% @ 1st frame
Dynamic Range	\geq 76dB
Sensitivity	360 lsb/uGy
SNR	47 dB @ (20000lsb)
MTF	75% @ (1 lp/mm) 48% @ (2 lp/mm) 29% @ (3 lp/mm)
DQE (2uGy)	64% @ (0 lp/mm) 38% @ (1 lp/mm) 21% @ (2 lp/mm)
Mechanical	
Dimension(H x W x D)	470 x 470 x 34.5 mm
Weight	10.6 kg / 12.7 kg
Sensor Protection Material	Carbon Fiber
Housing Material	Aluminum Alloy
Environmental	
Temperature Range	10~35°C (operating) ; -10~50°C (storage)
Humidity	30~70% RH (non-condensing)
Vibration	IEC 60068-2-64 Operation: 1G, 5-500Hz
Shock	IEC 60068-2-27 Operation: 2G, duration 11ms
Dust and Water Resistant	IPX0
Power	
Supply	100~240 VAC
Frequency	50/60 Hz
Consumption	20.5 W

